# **AQUA FLO**

# **Economy Reverse Osmosis System**

With the quality of our drinking water increasingly coming under question, people are now looking for alternative sources of quality water. Reverse Osmosis Drinking Water Systems provide the most convenient and economical solution.

Neatly stored under the counter, the Reverse Osmosis Drinking Water System provides you with clean and delicious water right from its own dedicated tap.




## FEEL GREAT... HYDRATE!

- ♦ 75% of your body is water
- Mild dehydration can cause headaches, dizziness, fatigue, dry skin and joint pain
- 33% of caloric intake comes from sugary drinks
- Water has 0 calories and helps suppress hunger



No lugging or storing heavy 40lb bottles, AquaFlo Solutions cost only pennies per litre.







75%

WATER

#### **Features:**

- The sediment filter screens out particulate material, such as dirt, sand, or rust, which may clog the other filters in the system.
- The activated carbon prefilter reduces chlorine which may damage the RO membrane filter.
- NSF Certified TFC 75 GPD reverse osmosis membrane provides up to 99% Total Dissolved Solids (TDS) rejection
- The polishing filter adsorbs any residual tastes and odors just before the water is delivered through the faucet.

- ◆ 3.2 Gallon NSF Certified plastic storage tank
- ◆ 3/8" outlet tubing for higher flows
- ◆ Automatic shut-off valve
- Exclusive serviceable check valve eliminates spring 'chatter' noise common in other RO's
- Quick connect fittings for ease of installation
- Plastic bracket
- Two separate wrenches for use on membrane cap and sump

Model #	Part #	Stage 1	Stage 2 and 3	Stage 4	Stage 5	Storage Tank	Faucet
RO75	20010073	Sediment Filter	Activated	Reverse	Activated	Plastic Tank - 3.2 Gallons	Standard
RO75BP *	20010074		Carbon Block Filter	Osmosis Membrane	Carbon Polishing Filter	Plastic Tank - 3.2 Gallons	



Booster Pump Model: RO75BP

### **Booster Pump Model also includes:**

- ◆ Pump mounted on RO to maintain constant water pressure to membrane
- ◆ Raises water pressure to ideal level for maximum efficiency
- Use on rural supplies with low pressure or highTDS
- Exclusive Auto Flush feature extends membrane life
- Self-priming and whisper quiet
- ◆ 24VAC transformer (included) from a standard 120VAC electrical outlet
- Flexible mounting plate, quick connect fittings and pressure shut-off switch

=	REVESE COMOS MAMBANA  NOTE OF THE PROPERTY OF	N

nis Membrane is Tested

This Membrane is Tested and Certified by NSF International against NSF/ANSI Standard 58 for material requirements only.

COMPONENT

Feed Water Guidelines				
Pressure	40 - 100 psi			
Temperature	40 - 77 ºF			
Total Dissolved Solids (TDS) <sup>1</sup>	0 - 2500 ppm (0 - 2500 mg/L)			
рН	5 - 10			
Chlorine <sup>2</sup>	0 - 3 ppm (0 - 3 mg/L)			
Chloramine	0 - 3 ppm (0 - 3 mg/L)			
Turbidity	0 - 10 NTU			
Hardness <sup>3</sup>	0 - 10 gpg			
Iron	0 - 1 ppm (0 - 1 mg/L)			
Bacterial Quality	Potable			

**AQUA FLO** 



Your Local Water Specialist